

### Indicators

#### ABS INDICATORS

#### VC-50 M



- Connectable to platforms up to 4 loadcells.
- ABS housing, high robustness.
- Back-light LCD display. 5 digits 24 mm high.
- Functions: piece counting, checkweighing, accumulation.
- Power: AC adapter (9V/800mA), internal rechargeable battery (6V/4Ah).
- Resolution: 6.000 divisions.
- CE approval, with DIBAL single loadcell and 4 loadcells platforms.

#### ABS INDICATORS

#### RW-I

- Back-light LCD display. 6 digits 22 mm high.
- Functions: zero, tare, unit conversion (kg/lb), accumulation, gross/net weight, and weight control with alarm.
- Connection: up to 4 loadcells platforms (minimum impedance: 350 Ohms).
- Robust ABS housing.
- Resolution: 1/30.000.
- Power: AC adapter (9V/800mA), internal rechargeable battery (6V/4Ah).



#### STAINLESS STEEL INDICATORS WITH LARGE DIGITS

#### VC-80 I



- Backlight LCD display, 5 ½ digits 52 mm high.
- Stainless steel housing.
- Easy to use. Front panel configuration.
- Connection: up to 4 loadcells platforms.
- Resolution: 6.000 divisions (OIML version. NON OIML version: 30.000 divisions).
- Functions: zero, tare, auto-off, keyboard blockade, weight control with alarm, animal weighing.
- Power: AC adapter (9V/800mA), internal rechargeable battery (6V/4Ah). Range: up to 90 hours (depending on use conditions).
- CE approval, with DIBAL single loadcell and 4 loadcells platforms

# Single Loadcell Platforms

## SINGLE LOADCELL PLATFORMS

## MA SERIES



- High robustness construction in steel (S-3545 and L-6080) or aluminium (M-4252).
- Stainless steel plate.
- Connectable to CELY and DIBAL indicators (others, please consult).

| Model           | S-3545      | M-4252       | L-6080   |
|-----------------|-------------|--------------|----------|
| Dimensions (cm) | 35 x 45     | 42 x 52      | 60 x 80  |
| Capacity (kg)   | 30, 60, 150 | 60, 150, 300 | 300, 600 |

**S-3545**  
**M-4252**  
**L-6080**

## SINGLE LOADCELL PLATFORMS

## ME SERIES

### • 3 versions available:

Iron structure, aluminium loadcell (PR).  
Stainless steel structure, protected aluminium loadcell (PC)\*.  
Stainless steel structure, stainless steel loadcell (PS).

- Stainless steel plate.
- Connectable to CELY and DIBAL indicators (others, please consult).

| Model           | S-3030        | M-4040      | L-6060       | XL-8080(**)   |
|-----------------|---------------|-------------|--------------|---------------|
| Dimensions (cm) | 30 x 30       | 40 x 40     | 60 x 60      | 80 x 80       |
| Capacity (kg)   | 6, 15, 30, 60 | 30, 60, 150 | 60, 150, 300 | 150, 300, 600 |

(\*) Platforms not suitable for salty environments (PC version). Available capacities: 60, 150 and 300 kg.

(\*\*) Models not available with CE approval in PC version.

**S-3030**  
**M-4040**  
**L-6060**  
**XL-8080**



## COLUMN KITS for ME platforms

### • 3 versions available:

Iron column kit for Dibal VD-310 ABS indicators.

Iron column kit for Cely VC-50 M indicators.

Stainless steel column kit for Dibal VD-310 st. steel and VD-330 st. steel, and Cely VC-80 I.



# Single Loadcell Bench Scales (Indicator + Platform + Column)

## BENCH SCALES WITH ABS OR ST. STEEL INDICATOR

## BAV SERIES

- Characteristics of the indicator: see VC-50 M and VC-80 I.
- Characteristics of the platform: see S-3545, M-4252, L-6080.
- Optional CE Approval.

| Model         | SVC              | MVC              | LVC              |
|---------------|------------------|------------------|------------------|
| Indicator     | VC-50 M, VC-80 I | VC-50 M, VC-80 I | VC-50 M, VC-80 I |
| Platform (cm) | 35 x 45          | 42 x 52          | 60 x 80          |
| Capacity (kg) | 30, 60, 150      | 60, 150, 300     | 300, 600         |



# Single Loadcell Bench Scales (Indicator + Platform + Column)

## BENCH SCALES WITH ABS OR ST. STEEL INDICATOR BEV SERIES

BR



- Characteristics of the indicator: see VC-40, VC-50 M and VC-80 I.
- Characteristics of the platform: Iron structure, aluminium loadcell. Stainless steel plate.
- Optional CE Approval.

| Model         | S-3030           | M-4040             | L-6060           | XL-8080          |
|---------------|------------------|--------------------|------------------|------------------|
| Indicator     | VC-50 M, VC-80 I | VC-50 M, VC-80 I   | VC-50 M, VC-80 I | VC-50 M, VC-80 I |
| Platform (cm) | 30 x 30          | 40 x 40            | 60 x 60          | 80 x 80          |
| Capacity (kg) | 6, 15, 30, 60    | 6, 15, 30, 60, 150 | 60, 150, 300     | 150, 300, 600    |

## BENCH SCALES WITH ABS OR ST. STEEL INDICATOR BEV SERIES

BC

- Characteristics of the indicator: see VC-50 M and VC-80 I.
- Characteristics of the platform: Stainless steel structure, protected aluminium loadcell. Stainless steel plate. Not suitable for salty environments.
- Optional CE Approval (except for 80 x 80 cm).

| Model         | M-4040           | L-6060           | XL-8080 <sup>(*)</sup> |
|---------------|------------------|------------------|------------------------|
| Indicator     | VC-50 M, VC-80 I | VC-50 M, VC-80 I | VC-50 M, VC-80 I       |
| Platform (cm) | 40 x 40          | 60 x 60          | 80 x 80                |
| Capacity (kg) | 60, 150          | 60, 150, 300     | 150, 300               |

<sup>(\*)</sup> Models not available with CE verification.



## BENCH SCALES WITH ST. STEEL INDICATOR BEV SERIES

BS



- Characteristics of the indicator: see VC-80 I.
- Characteristics of the platform: Stainless steel structure, stainless steel loadcell. Stainless steel plate.
- Optional CE Approval.

| Model         | S-3030        | M-4040      | L-6060       | XL-8080       |
|---------------|---------------|-------------|--------------|---------------|
| Indicator     | VC-80 I       | VC-80 I     | VC-80 I      | VC-80 I       |
| Platform (cm) | 30 x 30       | 40 x 40     | 60 x 60      | 80 x 80       |
| Capacity (kg) | 6, 15, 30, 60 | 30, 60, 150 | 60, 150, 300 | 150, 300, 600 |

## Crane Scales



### CRANE SCALES 100 - 200 kg

#### CR-100 / CR-200

- Capacity / Accuracy:  
100 kg – 50 g or 200 kg – 100 g.
- Robust ABS housing.
- 16,5 mm LCD backlight display.
- Functions: zero, tare, unit conversion (kg/lb), hold, auto-off.
- Power: 3 AA batteries (1,5 V).

### CRANE SCALES 300 - 600 kg

#### DR-300 / DR-600

- Capacity / Accuracy:  
300 kg – 50 g or 600 kg – 100 g.
- Robust ABS housing.
- Double LCD backlight display (frontal/back), 5 digits 25 mm high.
- Functions: zero, tare, unit conversion (kg/lb), hold, auto-off.
- Power: mains and rechargeable battery,  
(range: up to 35 hours, depending on use conditions).
- DR models are supplied with wireless remote control.



### CRANE SCALES 2.000 - 5.000 kg

#### BH-2 / BH-5

- Capacity/accuracy:  
2.000 kg - 1 kg or 5.000 kg - 2 kg.
- Display: LED - 1,2".
- Functions: zero, weight conversion (kg / lb),  
auto-off, hold display reading, divisions change.
- Rechargeable battery powered,  
(range: up to 60 hours, depending on use conditions).
- Includes wireless remote controller.



## Weighing Pallet Truck

### WEIGHING PALLET TRUCK

#### TW

- Capacity/accuracy: 2.000 kg - 1 kg.
- Display: backlight LCD, 5 ½ digits of 52 mm.
- 4 load cells.
- Functions: automatic zero tracking, weight conversion (kg / lb),  
pre-tare, gross/net weight and accumulation.
- Rechargeable battery powered.



# CELY

**DIBAL, S.A.**

Astintze, 24 (Pol. Ind. Neinver) - 48160 Derio - Vizcaya (SPAIN)

Tel.: (+34) 94 452 15 10 - Fax: (+34) 94 452 36 58 - [www.dibal.com](http://www.dibal.com) - [dibal@dibal.com](mailto:dibal@dibal.com)